

TKG852 WP SFinish&Eco

T1 Heat-pump tumble dryer with FragranceDos and SteamFinish for smooth laundry and a fresh fragrance.



- Fragrant laundry just the way you like it – FragranceDos
- The quick alternative to ironing w. steam smoothing – SteamFinish
- Precision drying of all textiles – PerfectDry
- Gentle laundry care thanks to the Miele honeycomb drum
- Always a close eye on consumption – EcoFeedback

Price \$ 2,999.00**

** GST inclusive

Construction type	
Suitable for stacking	•
Side-by-side	•
Slot-in	•
Door hinge	left
Model	
Heat pump dryer	•
Design	
Appliance colour	Lotus white
Control panel colour	Lotus white
Parameter buttons	Lotus white
Extra option buttons	Lotus white
Rotary selector colour	Lotus white
Control panel version	Slanted
Control type	Rotary selector
Display	1 line
Drying results	
FragranceDos	•
Perfect Dry	•
SteamFinish	•
Intelligent drum reversal	•
Gentle laundry care	
Patented honeycomb drum	•
User convenience	
Delay start up to 24 hours	•
Time left display	•
Programme sequence indicator	•
Drum lighting	LED
Choice of language	•
Condensate container	•
Integrated condensed water drainage	•
Efficiency and sustainability	
Maintenance-free heat exchanger	•
EcoFeedback function	•
EcoDry technology	•
ProfEco motor	•

TKG852 WP SFinish&Eco

T1 Heat-pump tumble dryer with FragranceDos and SteamFinish for smooth laundry and a fresh fragrance.



Drying programmes	
Automatic plus	•
Cottons (coloureds)	•
Minimum iron	•
Delicates	•
Shirts	•
Silks handcare	•
Woolens handcare	•
Steam smoothing	•
Express	•
Denim	•
Outerwear	•
Proofing	•
Sportswear	•
Cool air	•
Warm air	•
Basket programme	•
Gentle smoothing	•
Drying options	
Anti-crease	•
Gentle tumble	•
Freshen up	•
Buzzer	•
Automatic load control	•
Quality	
Enamelled front	•
Soft ribs	•
Safety	
PIN code lock	•
"Empty out container" indicator	•
"Clean filter" indication	•
Optical interface	•
Technical data	
Dimensions in mm (width)	596
Dimensions in mm (height)	850
Dimensions in mm (depth)	636
Appliance depth in mm with opened door	1,054
Weight in kg	62
Total rated load in kW	1.1
Voltage in V	230
Fuse rating in A	10
Length of supply lead in m	2
Contains fluorinated greenhouse gases	•
Hermetically sealed	•
Type of coolant	R134a